
ISABELLENHÜTTE
Innovation by Tradition

CMP // Size 2010



Features

- 2 W power rating at 70 °C
- Constant current up to 14 A (10 mOhm)
- High pulse power rating
- Good long-term stability
- Mounting: Reflow-, and IR-soldering
- AEC-Q200 qualified
- RoHS 2011/65/EU compliant

RoHS

Applications

- Current sensor for power hybrid applications
- Control systems for the automotive market
- Power modules
- Frequency converters
- Switch mode power supplies
- Driver for LED light systems

Technical data

Resistance values	**mOhm**	10 to 500
Tolerance	**%**	1 / 5
Temperature coefficient (20-60 °C)	**ppm/K**	<50
Applicable temperature range	**°C**	-65 to +170
Power rating $P_{70\,°C}$	**W**	2
Power rating $P_{120\,°C}$	**W**	1
Internal heat resistance (R_{thi})	**K/W**	<50
Dielectric withstanding voltage	**V AC/DC**	200
Inductance	**nH**	<3
Stability ($P_{120\,°C}$) deviation after 2000h T_K = Terminal temperature		<1.0 % (T_K=120 °C)

Ordering code


CMP - R010 - 1.0

- 1.0 ..... Tolerance
- R010 ..... Resistance value [Ohm] / "R" represents decimal point
- CMP ..... Type

CMP // SIZE 2010

Recommended solder profile

Reflow- and IR-soldering				
Temperature	**°C**	260	255	217
Time	**sec**	peak	40	90



Tape and reel information

Specification		DIN EN 60286-3
Tape width	**mm**	12
Reel size	**inch**	13
Parts per reel	**pcs**	12500
Packaging weight	**g**	481

Available standard resistance values and tolerances


Resistance values	Tolerance	
	1.0	5.0
R010	✓	✓
R012*		
R015	✓	✓
R020	✓	✓
R022	✓	✓
R025	✓	✓
R027*		
R030*		
R033	✓	
R036*		
R039*		
R043*		
R047	✓	✓
R050	✓	✓
R056*		
R062*		
R068*		
R075*		
R082	✓	

Resistance values	Tolerance	
	1.0	5.0
R091*		
R100	✓	✓
R120*		
R130*		
R150	✓	
R160*		
R180*		
R200	✓	
R220*		
R240*		
R250	✓	
R270*		
R300*		
R330*		
R360*		
R390*		
R430*		
R470*		
R500	✓	


✓ = available
* Values and tolerances on request

CMP // SIZE 2010


Temperature dependence of the electrical resistance of CMP resistors



Power derating curve



Mechanical dimensions [mm]




Type	L	W	H	A	B
CMP	5.08 ±0.2	2.54 ±0.2	0.4 ±0.15	0.7 ±0.2	0.4 ±0.15

Solder pad type	l	w	a
CMP	6.0	3.0	1.25

CMP // SIZE 2010

Maximum pulse energy respectively pulse power for permanent operation 120 °C



Specification

Parameters	Test conditions	Specified values
Temperature Cycling	2000 cycles (-65 °C to +170 °C)	±1.0 %
Low Temperature Storage	-65 °C for 250 h	±0.1 %
Resistance to Soldering Heat	260 °C for 10 sec / 8h steam aging	±0.3 %
Moisture Resistance	MIL-STD-202 method 106	±0.3 %
Mechanical Shock	100 g, 6 ms half sine	±0.2 %
Vibration, High Frequency	10 g, 10-2000 Hz, 24 h each axis	±0.2 %
Operational Life	2000 h, T_K = 120 °C at rated power	±1.0 %
High Temperature Exposure	2000 h / 170 °C	±1.0 %
Bias Humidity	+85 °C, 85 r.F., 1000 h, powered	±0.5 %

Disclaimer // All products, product specifications and data are subject to change without notice.

The product specifications do not expand or otherwise modify Isabellenhütte's terms and conditions of sale, including but not limited to, the warranty expressed therein. Isabellenhütte makes no warranty, representation or guarantee other than as set forth in its terms and conditions of sale.

Information provided in datasheets and/or specifications may vary from actual results in different applications. Any statements made by Isabellenhütte regarding the suitability of products for certain types of applications are based on its knowledge of typical requirements that are often placed on its products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in the application intended.

No license, express or implied, or otherwise, to any intellectual property rights is granted by this document.

Any and all liability arising out of the application or use of any product shall be as set forth in Isabellenhütte's terms and conditions of sale.